



QVIS® | PASSIVE HDCVI TRANSCEIVER SINGLE CHANNEL

FEATURES:

- 2 Pcs of TT-4K-105A
- No power required, simplified project wiring.
- Compatible with HDCVI/HDTV/ AHD.
- Plug and play, real-time transmit CCTV HD video signal, video is high quality and stable.
- Super interference rejection, built-in surge and transient protection, ESD.
- Screw terminal without pigtail, easier for installation.

SPECIFICATION	TT-4K-105A
Transmission Signal	1 Channel
Transmission Distance	HDCVI 720P: 400m / 1080P: 250m / 4MP & 4K: 200m HDTV 720P & 1080P: 250m / 4MP: 200m / 5MP & 4K: 180m AHD 720P: 300m / 1080P: 200m / 4MP: 200m / 5MP & 4K: 180m
Category Type	UTP CAT5 / 5E / 6
Coaxial Video Connector	BNC-M
Twisted-pair Video Connector	Screw interface
Compatible Format	HDCVI / HDTV / AHD
Resolution	720P / 1080P / 3MP / 4MP / 5MP / 4K
Anti-interference	>60db
ESD	1a contact discharge electricity level 3 1b air discharge electricity level 3 Per: IEC61000-4-2
Coaxial Cable Connector	2KV (common-code) Per: IEC1000-4-5
UTP Cable Connector	2KV (different-code) 2KV (common-code) Per: IEC1000-4-5
BNC Male	75 ohms
UTP Cable	1000 ohms
Shell	ABS
Colour	Black
MTBF	>1000H
Operating Temperature	-10°C ~ +55°C
Storage Temperature	-20°C ~ 70°C
Humidity	0 ~ 95% (non-condensing)