

# ETHERNET-OVER-COAX CONVERTER (10/100 Mbps)

# Titus

CODE: CON-01C



|                       |                   |                                                |
|-----------------------|-------------------|------------------------------------------------|
| Power                 |                   | DC12V                                          |
| Power Rate            |                   | <3W                                            |
| Standard              |                   | IEEE802.3; IEEE802.3U; IEEE802.3x; IEEE802.3af |
| Connectors            |                   | 1x RJ45; 1x BNC                                |
| Cabling Compatibility |                   | Coaxial Cable                                  |
| Data Rate             |                   | 10 Mbps / 100 Mbps                             |
| Transmission Distance |                   | 1200m                                          |
| Adjustment Switch     |                   | RX / TX                                        |
| LED Signal            | LAN               | Green LED                                      |
|                       | LRE               | Green LED                                      |
|                       | TX                | Green LED                                      |
|                       | RX                | Red LED                                        |
| Protection            | Power Port        | 2KV / 1KA; Per IEC61000-4-5                    |
|                       | Coaxial Port      | 2KV; Per IEC61000-4-5                          |
|                       | RJ45 Port         | 2KV / 4KV (Common Mode); Per IEC61000-4-5      |
| ESD                   | Contact Discharge | Level 3                                        |
|                       | Air Discharge     | Level 3                                        |
|                       | Complies to       | IEC61000-4-2                                   |

# ETHERNET-OVER-COAX CONVERTER (10/100 Mbps)



CODE: CON-01C

|                     |                                 |
|---------------------|---------------------------------|
| MTBF (Stability)    | >20,000h                        |
| Storage Temperature | −20°C to +70°C (−4°F to +158°F) |
| Working Temperature | 0°C to +55°C (32°F to +131°F)   |
| Working Humidity    | Less than 95% (RH)              |
| Casing              | Black Aluminium                 |
| Product Dimensions  | 80mm x 64mm x 25.5mm            |
| Net Weight          | 100g                            |