

5MP

FULL-COLOUR HD ANALOGUE TURRET CAMERA

Titus

CODE: TD-5COL-HD-TUR-FW



FULL
COLOUR



HD
ANALOGUE
INPUT



40m
LED
RANGE



IP67
INGRESS
PROTECTION



AUDIO
BUILT-IN
MIC



Camera

Image Sensor	5MP CMOS
Image Resolution	5MP (2880 x 1620)
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25s to 1/100,000s; NTSC: 1/25s to 1/100,000s
Minimum Illumination	0.005 lux @ F1.6 (White Light On)
S/N Ratio	>65dB
Illumination Distance	40m (131.23 ft.)
Illuminator On / Off Control	Auto / Manual
Illuminator Number	2
Pan / Tilt / Rotation Range	Pan: 0°-360°; Tilt: 0°-78°; Rotation: 0°-360°

5MP

FULL-COLOUR HD ANALOGUE TURRET CAMERA



CODE: TD-5COL-HD-TUR-FW



Lens Information

Lens Type	Fixed Focal			
Lens Mount	M12			
Focal Length	2.8mm			
Maximum Aperture	F1.6			
Field of View	Horizontal: 113°; Vertical: 60°; Diagonal: 132°			
Iris Control	Fixed			
Close Focus Distance	1m (3.28 ft.)			
DORI Distance	Detect	Observe	Recognise	Identify
	61.2m (200.79 ft.)	24.5m (80.39 ft.)	12.2m (40.03 ft.)	6.1m (20.01 ft.)



Video

Video Frame Rate	CVI: PAL: 5MP @ 25fps; 4MP @ 25fps; 1080P @ 25fps NTSC: 5MP @ 25fps; 4MP @ 30fps; 1080P @ 30fps
	AHD: PAL: 4MP @ 25fps; NTSC: 4MP @ 30fps
	TVI: PAL: 4MP @ 25fps; NTSC: 4MP @ 30fps
	CVBS: PAL: 960H; NTSC: 960H
Resolution	5MP (2880 x 1620); 4MP (2560 x 1440); 1080P / 2MP (1920 x 1080); 960H (960 x 576 / 960 x 480)
BLC	BLC / HLC / WDR
WDR	DWDR
White Balance	Auto; Area White Balance
Gain Control	Auto; Manual

5MP

FULL-COLOUR TURRET CAMERA



CODE: TD-5COL-HD-TUR-FW

Video

Noise Reduction	2D NR
Smart Illumination	Supported
Mirror	Supported
Privacy Masking	Supported (8 Areas)

Certification

Certifications	- CE: EN55032: 2015; EN61000-3-2: 2014; EN61000-3-3: 2013; EN55024: 2010+A1: 2015; EN55035: 2017; EN50130-4: 2011+A1: 2014; EN62368-1: 2014+A11 - FCC: 47 CFR FCC Part 15, Subpart B; ANSI C63.4-2014 - UL/CUL:UL62368-1 & CAN/CSA C22.2 No. 62368-1-14
----------------	---

Ports

Video Output	CVI; TVI; AHD; CVBS Outputs by 1x BNC
Audio Input	1 Channel Built-In Mic (-A)

Parameters & Dimensions

Power Supply	12VDC $\pm$ 30%
Power Consumption	Up to 5W (12VDC; Warm Light On)
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Working Temperature	-40°C to +60°C (-40°F to +140°F)
Working Humidity	Less than 95% (RH)
Protection	IP67
Casing	Metal
Product Dimensions	93.6mm x Φ 106mm (3.69" x Φ 4.17")
Net Weight	480g (1.06lb)
Gross Weight	670g (1.48lb)