



Fixed Lens Bullet Camera

CODE: BULLETVIP4K-FG-A



Fixed Lens



Built-In Microphone



30m IR Range



PoE Support

Camera

Image Sensor	1/2.5" CMOS
Video Compression	H.265 / H.264
Resolution	8MP, 2K, 3MP, 2MP (1 to 25fps)
Minimum Illumination	0.024 lux at F1.2 (AGC on); 0.068 lux at F1.62.0 (AGC on); 0 lux with IR or LED
IR Range	30m
Lens	2.8mm
Focus	Fixed
Image Correction	BLC, HLC, WDR, Defog, Digital NR

Interfaces

Network	RJ45
Audio	1CH audio input
Video Output	CVBS (BNC x1)

Functions

Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Online Connection	Simultaneous multi-stream real time transmission
Maximum Users for Monitoring	Up to 10 users (simultaneous)
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, SNMP, 802.1x, UPnP, HTTPS, QoS



Fixed Lens Bullet Camera

CODE: BULLETVIP4K-FG-A


IP

8^{4K}
MP

Functions (continued)

Interface Protocol	ONVIF, GB-T/28181-2011
AI Events	Line Crossing Detection, Region Intrusion Detection (People & Vehicle), Video Abnormality, Face Detection People Counting
Additional Functions	Watermark, Video Mask, Heartbeat, Password Protection

Compatible Accessories



Cable Management Ring

CODE: VIP-RING-03-GR

Parameters & Dimensions

Power Supply	DC12V / PoE
Power Consumption	< 8W
Operating Environment	Temperature: -30°C to +60°C; Humidity: Less than 95% (non-condensing)
Dimensions	Φ86.7mm × 219.4mm
Weight	0.61kg
Installation	Ceiling or wall mounted
Protection Grade	IP66
Certificate	UKCA, CE, PSTI 2023, RoHS