

QPac Linear Batten (1500mm)

Surface & Suspended Range

CODE: QPAC-60-1500TC

QVIS[®]
LED LIGHTING




**QUICK RELEASE -
EASILY REMOVE
THE DIFFUSER
FROM THE BASE**




Specification	QPac
System Power	60W
Driver Manufacturer	Q-Drive
LED Chipset	Epistar
Colour Rendering Index	>80
Lumen Output	7200Lm
LED Efficacy	120 Lm/cW
Power Factor	>0.9
Dimmable	On Request
IP Rating	IP20
Colour Temperature	3000K/4000K/6000K
Beam Spread	120°
Housing Material	Iron
Diffuser Material	Polycarbonate
Operating Temperature	-20 to +40°C
Input Voltage	220-240V
Dimensions	1500mm x 72mm x 72.5mm
Weight	2.08kg
MacAdam Step	<3
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

TECHNICAL DRAWINGS



A = 1500mm C = 72.5mm
B = 72mm

LUMINOUS INTENSITY DISTRIBUTION



* Warranty terms and conditions apply

Information is subject to change and can be withdrawn without notice

For further information on our products or terms and conditions visit our website www.qvis.co.uk/lighting or email: sales@qvislighting.com