

QStorm Pro

Switchable Vapour Proof

CODE: QS-PRO-WS-600TC/EM



-  **170** High LED Efficacy
-  IK08 Impact Resistance
-  Wattage Switchable
-  Tri-Colour (3000K/4000K/5700K)

Dimensions



Power [Selectable]	Efficacy	Output	Kelvin
11W [Emergency 3W]	170Lm/cW	1870Lm [Emergency 510Lm]	Tri-Colour: 3000K, 4000K or 5700K
14W [Emergency 3W]	170Lm/cW	2380Lm [Emergency 510Lm]	
16W [Emergency 3W]	170Lm/cW	2720Lm [Emergency 510Lm]	
19W [Emergency 3W]	170Lm/cW	3230Lm [Emergency 510Lm]	

Technical

Input Voltage	AC 200-240V
Colour Rendering Index	>80
Beam Spread	120°
Power Factor	>0.9
Operating Temp.	-20 to +40°C
Materials	Polycarbonate
IP Rating	IP66
IK Rating	IK08
Dimmable	On Request
Dimensions	663mm x 120mm x 76mm
Weight	1.16kg
MacAdam Step	<3
Lifetime	3 Hours [3W]
Lifetime	50,000 hours, L90-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

Light Source Energy Rating

Photometric Data

