

QBay Adjustable Low Bay

CODE: QBAY-WS-TC/EM

-  **Low-Glare Diffuser**
(Polycarbonate)
-  **IK08 Impact Resistance**
-  **Wattage Switchable**
-  **Tri-Colour** (4000K/5000K/6000K)

Dimensions



Power (Selectable)	Efficacy	Output	Kelvin
100W (Emergency 5W)	170Lm/cW	17000Lm (Emergency 850Lm)	Tri-Colour: 4000K, 5000K or 6000K
150W (Emergency 5W)	170Lm/cW	25500Lm (Emergency 850Lm)	
200W (Emergency 5W)	170Lm/cW	34000Lm (Emergency 850Lm)	

Technical

Input Voltage	AC 120-240V
Colour Rendering Index	>80
Side Wing Tilt Angle	-5° to 35°
Power Factor	>0.9
Operating Temp.	-20 to +50°C
Materials	Metal & Polycarbonate
IP Rating	IP40
IK Rating	IK08
Dimmable	1-10V (as Standard)
Dimensions	655mm x 366mm x 48mm
Weight	5.211kg
MacAdam Step	<3
Emergency Output	3 Hours [5W]
Lifetime	50,000 hours, L70-B10 (Ta 25 °C)
CE Standards	EN60598-1, EN62493, EN55015, EN61547, EN61000-3-2, EN61000-3-3, EN62722-1, EN62722-2-1 and EN50581
CE Directives	LVD, EMC, ERP & RoHS

A T G **C** Light Source Energy Rating

Photometric Data

